

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Blackhawk Foaming Coil Cleaner (4127-75)
Other means of identification	Not available
Recommended use	Cleaner
Recommended restrictions	None known.
Manufacturer	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US

2. Hazards Identification

Physical hazards	Gases under pressure	Liquefied gas
Health hazards	Serious eye damage/eye irritation	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Contains gas under pressure; may explode if heated. Causes serious eye damage.
Precautionary statement	
Prevention	Wear eye/face protection.
Response	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.
Storage	Protect from sunlight. Store in a well-ventilated place.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.95
Propane		74-98-6	2.05
Diethylene glycol monoethyl ether		111-90-0	2
Ethanol, 2-butoxy-		111-76-2	2
Sodium lauryl sulfate		151-21-3	1.9
Tetrasodium ethylenediamine tetraacetate		64-02-8	1.48
Sodium metasilicate		6834-92-0	0.24

4. First Aid Measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Suitable extinguishing media	Alcohol foam. Carbon dioxide. Dry chemical. Foam.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.
Explosion data	
Sensitivity to mechanical impact	Not available.
Sensitivity to static discharge	Not available.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment.
Conditions for safe storage, including any incompatibilities	Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls/Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethanol, 2-butoxy- (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Ethanol, 2-butoxy- (CAS 111-76-2)	TWA	24 mg/m3
		5 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Diethylene glycol monoethyl ether (CAS 111-90-0)	TWA	140 mg/m3
		25 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethanol, 2-butoxy- (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Chemical splash goggles.
Skin protection	
Hand protection	Wear protective gloves.
Other	Not available.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA).
Thermal hazards	Not applicable.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Compressed liquefied gas
Physical state	Gas.
Form	Liquefied gas.
Color	Clear
Odor	Lemon lime
Odor threshold	Not available.
pH	12.3
Melting point/freezing point	Not available.

Initial boiling point and boiling range	32 - 401 °F (0 - 205 °C)
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available
Flash point	Not available.
Evaporation rate	Not available
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	65 psi @ 70°F
Vapor density	Not available
Relative density	Not available.
Solubility(ies)	Not available Auto-ignition temperature Not available
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Flash point class	Not Flammable as per testing under UN Manual of Tests and Criteria Part 3, Section 31.5

10. Stability and Reactivity

Reactivity	Reacts vigorously with acids.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Reacts violently with strong acids. This product may react with oxidizing agents. Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Not corrosive to SAE 1020 Steel or non-clad Aluminum based on test data (UN Manual of Tests and Criteria, Part III, Section 37.1 -Corrosion to metals). Oxidizing agents. Acids.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
Information on likely routes of exposure	
Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	US GHS: Not corrosive to skin based on in-vitro test data (OECD Guideline 435 - Corrositex®). CANADA WHMIS: As per Policy Issue Sheet Number 60, strongly acidic or alkaline substances with a demonstrated pH of 2 or less or 11.5 or greater, need not be tested for primary dermal irritation, owing to their predictable corrosive properties.
US. NIOSH: Pocket Guide to Chemical Hazards	
Ethanol, 2-butoxy- (CAS 111-76-2)	Can be absorbed through the skin.
Eye contact	Causes serious eye damage.
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Information on toxicological effects	
Acute toxicity	

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	276000 ppm, 4 Hours
		658 mg/l/4h
<i>Oral</i>		
LD50	Not available	
Diethylene glycol monoethyl ether (CAS 111-90-0)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	5900 mg/kg
	Mouse	6000 mg/kg
	Rabbit	6000 mg/kg
	Rat	6000 mg/kg
<i>Inhalation</i>		
LC50		
	Rat	5240 mg/l/4h
<i>Oral</i>		
LD50	Guinea pig	3000 mg/kg
	Rabbit	3620 mg/kg
	Rat	5500 mg/kg
		1920 mg/kg
Ethanol, 2-butoxy- (CAS 111-76-2)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	207 mg/kg
	Rabbit	400 mg/kg
		220 mg/kg
		99 mg/kg
	Rat	99 mg/kg
<i>Inhalation</i>		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
		2.2 mg/l, 4 Hours
<i>Oral</i>		
LD50	Guinea pig	1200 mg/kg
	Mouse	1200 mg/kg
	Rabbit	320 mg/kg
	Rat	470 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.8 mg/l, 15 Minutes
<i>Oral</i>		
LD50	Not available	
Sodium lauryl sulfate (CAS 151-21-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	580 mg/kg

Components	Species	Test Results
<i>Inhalation</i> LC50	Rat	> 3900 mg/m3, 1 hr
<i>Oral</i> LD50	Rat	1288 mg/kg
Sodium metasilicate (CAS 6834-92-0)		
Acute		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Mouse	2400 mg/kg
	Rat	1153 mg/kg
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)		
Acute		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Rat	1658 mg/kg
Skin corrosion/irritation	US GHS: Not corrosive to skin based on in-vitro test data (OECD Guideline 435 - Corrositex®). CANADA WHMIS: As per Policy Issue Sheet Number 60, strongly acidic or alkaline substances with a demonstrated pH of 2 or less or 11.5 or greater, need not be tested for primary dermal irritation, owing to their predictable corrosive properties.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
US. NIOSH: Pocket Guide to Chemical Hazards		
Ethanol, 2-butoxy- (CAS 111-76-2)	Can be absorbed through the skin.	
US. NIOSH: Pocket Guide to Chemical Hazards		
Ethanol, 2-butoxy- (CAS 111-76-2)	Can be absorbed through the skin.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.	
ACGIH Carcinogens		
Ethanol, 2-butoxy- (CAS 111-76-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethanol, 2-butoxy- (CAS 111-76-2)	Volume 88 - 3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Teratogenicity	Not available.	

Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful.
Further information	Not available.
Name of Toxicologically Synergistic Products	Not available.

12. Ecological Information

Ecotoxicity	See below		
Components		Species	Test Results
Diethylene glycol monoethyl ether (CAS 111-90-0)			
Crustacea	EC50	Daphnia	4305 mg/L, 48 Hours
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 10000 mg/l, 96 hours
Ethanol, 2-butoxy- (CAS 111-76-2)			
Crustacea	EC50	Daphnia	1819 mg/L, 48 Hours
Aquatic			
Fish	LC50	Inland silverside (<i>Menidia beryllina</i>)	1250 mg/l, 96 hours
Sodium lauryl sulfate (CAS 151-21-3)			
Algae	IC50	Algae	53 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1.8 mg/L, 48 Hours
Aquatic			
Fish	LC50	Carp, hawk fish (<i>Cirrhinus mrigala</i>)	1.36 mg/l, 96 hours
Sodium metasilicate (CAS 6834-92-0)			
Aquatic			
Crustacea	EC50	Water flea (<i>Ceriodaphnia dubia</i>)	0.28 - 0.57 mg/l, 48 hours
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>)	1800 mg/l, 96 hours
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)			
Algae	EC50	Algae	1.01 mg/L, 72 Hours
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	610 mg/l, 24 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	472 - 500 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS, non-flammable
Hazard class	Limited Quantity - Canada
Special provisions	80

IATA/ICAO (Air)

Basic shipping requirements:


UN number	UN1950
Proper shipping name	Aerosols, non-flammable
Hazard class	Limited Quantity - IATA
ERG code	2L

IMDG (Marine Transport)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS
Hazard class	Limited Quantity - US

DOT; IMDG; TDG



IATA



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Canada CEPA Schedule I: Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Butane (CAS 106-97-8) 1 TONNES

Ethanol, 2-butoxy- (CAS 111-76-2) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

Canada Priority Substances List (Second List): Listed substance

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Canada WHMIS Ingredient Disclosure: Threshold limits

Butane (CAS 106-97-8)	1 %
Diethylene glycol monoethyl ether (CAS 111-90-0)	1 %
Ethanol, 2-butoxy- (CAS 111-76-2)	1 %
Sodium lauryl sulfate (CAS 151-21-3)	1 %
Sodium metasilicate (CAS 6834-92-0)	1 %

WHMIS status Controlled
WHMIS classification Class A - Compressed Gas, Class E - Corrosive Material

WHMIS labeling

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Diethylene glycol monoethyl ether (CAS 111-90-0)	1.0 % N230
Ethanol, 2-butoxy- (CAS 111-76-2)	1.0 % N230

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed. N230
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed. N230

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8)	Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.
Propane (CAS 74-98-6)	Listed.

US CAA Section 111 Volatile Organic Compounds: Listed substance

Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed.
Ethanol, 2-butoxy- (CAS 111-76-2)	Listed.

US CAA Section 112(r) Accidental Release Prevention - Regulated Flammable Substance: Listed substance

Butane (CAS 106-97-8)	Regulated flammable substance.
Propane (CAS 74-98-6)	Regulated flammable substance.

US CAA Section 112(r) Accidental Release Prevention: Threshold quantity

Butane (CAS 106-97-8)	10000 LBS
Propane (CAS 74-98-6)	10000 LBS

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)	Listed.
Propane (CAS 74-98-6)	Listed.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethylene glycol monoethyl ether (CAS 111-90-0)	Listed.
--	---------

US CAA Section 612 SNAP Program: Listed substance

Butane (CAS 106-97-8)	Listed.
Propane (CAS 74-98-6)	Listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - No
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Diethylene glycol monoethyl ether	111-90-0	2
Ethanol, 2-butoxy-	111-76-2	2

Other federal regulations

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130) Hazardous substance

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Butane (CAS 106-97-8) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Formaldehyde (CAS 50-00-0) Listed.

US - Illinois Chemical Safety Act: Listed substance

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

US - Louisiana Spill Reporting List: Reportable quantity (total mass into atmosphere)

Diethylene glycol monoethyl ether (CAS 111-90-0) 100 LBS
Ethanol, 2-butoxy- (CAS 111-76-2) 100 LBS

US - Louisiana Spill Reporting: Listed substance

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

US - Minnesota Haz Subs: Listed substance

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

US - Texas Effects Screening Levels: Listed substance

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.
Sodium lauryl sulfate (CAS 151-21-3) Listed.
Sodium metasilicate (CAS 6834-92-0) Listed.
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8) Listed.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

US. Pennsylvania RTK - Hazardous Substances

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

US. Rhode Island RTK

Butane (CAS 106-97-8) Listed.
Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.
Ethanol, 2-butoxy- (CAS 111-76-2) Listed.
Propane (CAS 74-98-6) Listed.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

30-October-2014

Effective date

31-October-2014

Expiry date

31-October-2017

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.